

## UVA HAND LED



### HAND-HELD LED-UV

Mobile and durable

### FEATURES

- High intensity
- Homogenous intensity distribution
- Long service life
- Different wavelengths
- Handy and lightweight
- For all current supply voltages and frequencies

### BENEFITS

- Excellent production results within seconds
- Multifunctional
- Reliable and long-living
- No warm-up
- No standby time
- Low power consumption

## UVA HAND LED

UVA Hand LED is a high-intensity hand-held LED-UV lamp. It is easy to transport, ergonomically designed and ideal for mobile use. Its intensive irradiation ensures reliable production results within seconds. A homogeneous intensity distribution is guaranteed by the arrangement of the LEDs. The typical service life of a LED is longer than 20,000 hours\*. The UVA Hand LED can be switched on and off as often as necessary. It does not require a warm-up or cooling phase.

It is available with emitted wavelengths of 365 or 405 nm +/- 10 nm. This allows an adaption of the hand lamp to the respective application.

### FLEXIBLE APPLICATIONS

UVA Hand LED is especially apt for curing UV reactive adhesives and sealants. The high intensity at 365 nm enables reliable results for fluorescence tests.

### FIELDS OF APPLICATION

- Curing of UV reactive adhesives when joining glass, plastics and metals
- Curing of UV reactive compounds on electrical and electronic components
- Production and repair of plastic parts with UV curing polyester resins
- Particle control in clean rooms
- Authenticity testing
- Fluorescent testing for quality control purposes in plant engineering, in the aviation industry (certificated according to ASTM E3022 and other certifications on request), as well as in the textile and printing industry

### PRACTICAL AND SAFE

UVA Hand LED does not need any external power supply. The lamp unit is directly connected to the mains supply and thus can be used very flexibly.

High-strength aluminium and polycarbonate lamp housings make UVA Hand LED a very durable product.

A robust carrying case is optionally available for safe transportation.



UVA Hand LED

### TECHNICAL DATA

Power supply	90 - 264 V AC / 47 - 63 H
Intensity **)	365 nm: 200 mW/cm <sup>2</sup> 405 nm: 350 mW/cm <sup>2</sup>
Dimension of output window	137 x 75 mm
Weight lamp unit	1.9 kg
Power input	70 W

\*) Typical service life under specified operating conditions

\*\*\*) Measured with Hoenle UV Meter and LED surface sensor, distance 20 mm

**Hoenle Eleco**  
125, av Louis Roche  
Z.A. des Basses Noels  
92238 Gennevilliers Cedex  
France

T. +33 1 47 92 41 80  
eleco@hoenle-eleco.com

[www.hoenle-eleco.com](http://www.hoenle-eleco.com)

Operating parameters depend on production characteristics and may differ from the foregoing information. We reserve the right to modify technical data. © Copyright Hoenle Eleco. Updated 09/25

